

### Mini Speed Dome Camera LDS-200NM


True Day & Night, DSS, DNR

The camera, with up to 100x zoom, is ideal for indoor use. It is a Speed Dome Camera, which can clearly observe a subject in low light conditions with added DSS functions.



## FEATURES

- 410K PIXEL, 1/4" Sony Super HAD CCD
- 10x Optical Zoom Lens, Auto Focus, Auto Iris and Zoom Tracking
- Horizontal resolution of 500 TVL at color mode and 570 TVL at B/W mode
- Day & Night (ICR)
- Digital Noise Reduction (DNR)
- Back Light compensation
- Smart Zoom
- 250 Preset Positions
- Swing, Group, Spiral, Auto Flip, Alarm
- 4 Privacy Zone Masking



(UNIT: mm)

## SPECIFICATIONS

Signal system	NTSC	PAL
Image sensor	1/4" Sony Super HAD CCD	
Horizontal resolution	More than 520 TVL, B/W 570 TVL	
Effective pixels	768(H) X 494(V),	752(H) X 582(V)
Scanning Frequency	15.734KHz(H), 4Hz(V)	15.625KHz(H), 50Hz(V)
Lens	10x Optical zoom, f=3.8-38mm, F 1.8	
Digital zoom	10x (Total zoom 100x)	
Angle of view	Approx 51.2° (Wide), Approx 5.58° (Tele),	
Minimum illumination	0.0007 Lux @ F1.8	
Luminance S/N ratio	More than 50dB	
Video output	1 Vp-p Composite video output 75Ω	
Focus mode	Auto / Manual / Oneshot	
SSNR	Off / Low / Middle / High	
Back Light	Off / Low / Middle / High	
Shutter speed	Auto / 1/128 ~ 1/120,000 sec	
Sharpness control	Level (0 - 10)	
Motion Detection	On/Off	
Alarm in/out	4 Inputs / 1 Relay Output	
Pan/Tilt angle	360° Endless / 92°	
Pan speed	0.1° ~ 240°/sec (64 Levels)	
Preset point	250 Presets	
Preset Speed	Max 360°/sec (64 Levels)	
Privacy zones masking	4 Zones	
Operating temperature	- 10°C ~ 50°C (-14°F ~ 122°F)	
Communication system	RS-485 / 422	
OSD	Built-in	
Operating humidity	Less than 90%RH	
Dimensions	104mm (Diameter) x 138 mm (Height)	
Weight	About 1.1 Lb	
Construction	PC body , Clear vandal bubble (PC)	
Power consumption	5W	
Power supply	DC12V 0.8A (Option: AC24V)	

Specifications are subject to change without notice